

Audi Service

## 2009 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95	35/75/115
Kilometres (in thousands)	8/40/70/100/130/160/200	25/85/145	55/115/175
Engine Oil/Oil Filter – change oil and replace filter	•	•	•
Wiper Blades – check condition and replace if necessary	•	•	•
Wiper/Washer/Headlight Washer – check adjustment and function,	•	•	•
add fluid if necessary			
Tires and Spare – check for wear and damage, check pressure	•		115K only
<ul> <li>check for wear and damage, check pressure and renewal date of tire set (where applicable)</li> </ul>		•	35K/75K only
AdBlue Fluid – fill completely with fresh fluid (23 liters)	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only
Tires – rotate	5K only		
Service Reminder Display – reset	•	•	•
Brake System – check for damage, leaks, pad thickness, fluid level	•	•	•
Cooling System – check level, add if necessary		•	•
Exhaust System – check for damage, leaks		•	•
Engine On Board Diagnostics – check fault memory		A3, A4 Cabriolet, S4, A6, S6, A8, S8 only	A3, A4 Cabriolet, S4, A6, S6, A8, S8 only
Engine Compartment – check for leaks		•	•
Battery – check and replace if necessary		•	•
Dust and Pollen Filter – replace		•	•
Automatic Transmission and Final Drive – check for leaks Manual Transmission and Final Drive – check for leaks		•	•
			•
Haldex Clutch – change oil			A3, TT only
Front Axle – check for excessive play, check dust seals on ball joints and tie rod ends		A3, A4 Cabriolet, S4, A6, S6, A8, S8 only	•
Lights – check all lights, check headlight adjustment		A8, S8 only	A3, A4 Cabriolet, S4, A6, S6, A8, S8 only
Drive Shaft Boots – check		•	•
Doors – lubricate doors, check straps and hood latch		A8, S8 only	Except A8, S8
Spark Plugs – replace at 35,000 miles or 3 years, whichever occurs first. Then, every 40,000 miles or 3 years, whichever occurs first.			<ul> <li>35K/115K only: A4 2.0L</li> <li>TFSI, A5 2.0L TFSI,</li> <li>TTS, A3 3.2L, TT 3.2L,</li> <li>A8 6.0L only</li> </ul>
– replace at 55,000 miles or 6 years, whichever occurs first. Then, every 60,000 miles or 6 years, whichever occurs first.		<ul> <li>55K only: except A3 3.2L, TT 3.2L, A4 2.0L TFSI, A5 2.0L TFSI, TTS, A8 6.0L</li> </ul>	
– replace at 75,000 miles			75K only: A3 3.2L, TT 3.2L, A4 2.0L TFSI, A5 2.0L TFSI, TTS,
Continuously Variable Transmission (multitronic) – change ATF			A8 6.0L only
Power Steering Fluid – check, add if necessary			•
Air Cleaner – clean housing, replace filter element		55K only: except Audi 07 4.2L, A8 6.0L	<ul> <li>35K only: A8 6.0L only</li> <li>75K only: Audi Q7 4.2L, A8 6.0L only</li> <li>115K only: A8 6.0L only</li> </ul>
Ribbed V Belt and Tensioner – check condition and replace if necessary		Audi R8 only	Audi Q7 3.6L, A8 6.0L, A8 6.0L, Audi R8 only
Ribbed V Belt – replace			75K only: S4 only
<ul> <li>check condition, replace if necessary. Check tension of belt drive with manual tensioner and retension if necessary.</li> </ul>			75K only: V6 FSI, V6 TFSI (rear belt), 2.0L TFSI, 5.2L FSI,
<ul> <li>– replace only the V belt for the compressor drive</li> </ul>			4.2L V8 FSI 75K only: 3.0 TFSI only
Snow Screen for Air Cleaner – clean		A4, A5, S5 and A6 only	A4, A5, S5 and A6 only
Underbody – check for damage and leaks		and A6 only	and A6 only
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air conditioning, ASL Automatic Shift Lock and power accessories		•	•
Rear Lid Hinges – lubricate		A8, S8 only	A8, S8 only
Horn – check function		• Ad, 38 Univ	• A8, 38 0my
Brake Discs – check thickness		-	•
Lights – check all lights via instrument cluster. Check license plate light from the rear of the vehicle			<ul> <li>Audi Q7, A4, S4, Audi Q5, TT, A5, S5, Audi R8 only</li> </ul>
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			
DSG/S Tronic – change oil and replace filter element			A3, TT only
Fuel Filter – remove water		Audi Q7 3.0L TDI only	
– replace			Audi Q7 3.0L TDI only
Diesel Particle Filter (DPF) – check ash content within the DPF. Replace DPF with an ash content greater than or equal to .46 liters.	125K only: Audi Q7 3.0L TDI only		
an aon contont groutor than or equal to .+0 liters.		•	•

At 110k miles (175 km) replace timing belt on Audi TT 2.0T with front wheel drive and A4 Cabriolet 2.0T only. Check condition of timing belt tensioning system, dampening pulleys, and idler pulleys and replace if necessary (Audi TT 2.0T with front wheel drive and A4 Cabriolet 2.0T only). Brake Fluid – replace every 2 years regardless of mileage. Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A4/S4 Cabriolet and A5/S5 Cabriolet only). Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options events of the standard features and options

subject to change without notice.