

## 2011 Scheduled Maintenance Intervals

Miles (in thousands)	5/25/45/65/85/105/125	15/55/95/135	35/75/115
Kilometers (in thousands)	8/40/70/100/130/160/190	25/85/145/205	55/115/175
Engine Oil /Oil Eilter - change oil and replace filter	•	•	
Engine Oil/Oil Filter – change oil and replace filter  AdBlue Fluid – fill completely with fresh fluid (maximum capacity: 23 liters) and adapt	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only	Audi Q7 3.0L TDI only
earned values for AdBlue tank under guided fault finding after filling fluid	Audi Q7 3.0L IDI only	Audi Q7 3.0L IDI only	Audi Q7 3.0L TDI only
Cooling System – check level, add if necessary		•	•
Engine Compartment – check for leaks		•	•
Battery - check for clean terminals (no corrosion), properly mounted housing,		•	•
and no damage; replace if necessary. Also, check the acid level of battery only if the level can be seen through the housing and fill if necessary			
<b>Dust and Pollen Filter</b> – replace			•
<b>Spark Plugs</b> – replace at 35,000 miles or 3 years, whichever occurs first. Thereafter, every 40,000 miles or 3 years, whichever occurs first			<ul> <li>A4, A5, Q5, TT and TTS with 2.0L TFSI engine only</li> </ul>
<ul> <li>replace at 55,000 miles or 6 years, whichever occurs first.</li> <li>Thereafter, every 60,000 miles or 6 years, whichever occurs first</li> </ul>		<ul> <li>55K only: except A4, A5, Q5, TT and TTS with 2.0L TFSI engine</li> </ul>	
Power Steering Fluid - check, add if necessary			•
Air Cleaner – clean housing, replace filter element		55K only: except Audi Q7 4.2L	75K only: Audi Q7 4.2L on
Ribbed V Belt and Tensioner – check condition and replace if necessary		R8, R8 Spyder only	
Ribbed V Belt – check condition, replace if necessary. Check tension of belt drive		- ···, ··· - · · · · · · · · · · · · · ·	Audi Q7 3.6L, R8, R8 Spyder only
with manual tensioner and retension if necessary			75K only: V6 FSI, V6 TFSI (rear belt), 2.0L TFSI, 5.2l FSI, 4.2L V8 FSI only
– replace only the V belt for the compressor drive			75K only: 3.0L TFSI only
		A4, S4, A5, S5 and A6 only	A4, S4, A5, S5 and A6 onl
Fuel Filter – replace		<ul> <li>A3 2.0L TDI and Audi Q7 3.0L TDI only</li> </ul>	<ul> <li>A3 2.0L TDI and Audi Q7 3</li> <li>TDI only</li> </ul>
<b>Diesel Particulate Filter (DPF)</b> – check ash loading according to manufacturer's work procedure, replace* if necessary	<ul> <li>USA: 125K only: Audi Q7 3.0L TDI, A3 2.0L TDI only</li> <li>Canada: 205,000 km only: Audi Q7 3.0L TDI, A3 2.0L TDI only</li> </ul>		
Plenum Panel – remove cover for plenum panel to check water drain and clean if necessary		•	•
Fires and Spare Wheel – check for wear and damage, check tire pressure, reset Tire Pressure Monitoring System (TPMS)	•		
<ul> <li>- check for wear and damage, check tire pressure and renewal date of tire repair set (where applicable), reset Tire Pressure Monitoring System (TPMS)</li> </ul>		•	•
Fires – rotate, reset TPMS	SK only		
Wiper Blades – check condition and replace if necessary	•	•	•
Wiper/Washer/Headlight Washer – check adjustment and function, add fluid if necessary	•	•	
Interior Lights – check all interior lights, glove box illumination, control lights and MMI (if applicable)			•
Front Lighting – check function of parking lights, low beams, high beams, fog lights, blinkers and hazard lights		•	•
Rear Lighting – check function of brake lights (including third brake light), tail lights, back-up lights, rear fog lights, license plate lights, blinkers and hazard lights		•	•
Service Reminder Display – reset	•	•	
Horn – check function		•	•
Door Hinges and Straps – Lubricate		<ul> <li>Audi Q7, A3, A6, S6, TT, TTS, R8 and R8 Spyder only</li> </ul>	
<b>Doors</b> – lubricate door hinges, straps, locks and hood latch			•
Hood Lid Hinges – lubricate		Audi R8, R8 Spyder, TT and	Audi R8, R8 Spyder, TT and
-		TTS only	TTS only
Sliding Roof – clean guide rails and lubricate with grease	•	_	
Brake System – check for damage, leaks, pad thickness, fluid level	•	•	•
Brake Discs – check thickness			•
Exhaust System – check for damage, leaks		•	•
Front and Rear Axle – check for excessive play, check dust seals on ball joints and tie rod ends		•	•
Drive Shaft Boots - check		•	•
Automatic Transmission and Final Drive – check for leaks		•	•
Automatic Transmission Fluid – replace (U.S. only)			USA: Audi Q7 only
Manual Transmission and Final Drive – check for leaks		•	•
Continuously Variable Transmission (multitronic) – change ATF			•
Haldex Clutch – change oil			A3, TT, TTS only
DSG/S Tronic – change oil and replace filter element			A3, TT, TTS, S4 and S5 onl
Underbody – check for damage and leaks		•	•
Road Test – check braking, kick-down, steering, electrical, heating and ventilation systems, air		•	•
conditioning, ASL Automatic Shift Lock, power accessories and reset driver information display Fiming Belt – replace at 110K miles (175,000 km) on Audi TTS or 130K miles (205,000 km) on Audi A3 2.0L TI	OI only. Check condition of timing h	elt tensionina system, damno	ening pulleys, and idler

**Brake Fluid** – replace every 2 years regardless of mileage

Cloth Top – check function and rollover protection every 2 years regardless of mileage (Audi A5/S5 Cabriolet, R8 Spyder only)

Crash Active Headrest – check function every 2 years regardless of miles/kilometers (A8 only)

\*If DPF replacement is not necessary, perform check every 20,000 miles (30,000 km) thereafter until replacement becomes necessary. Subsequent DPF replacement interval is a minimum of 120,000 miles (200,000 km), thereafter.

Audi of America, Inc. believes the information and specifications to be correct at the time of printing. Specifications, maintenance intervals, standard features and options subject to change without notice.